

IT PRINTS AND PRINTS AND PRINTS ...

Allow us to present the all-rounder for reducing workloads and saving space. The 4056i/5056i/6056i A3 b/w multifunctional systems make light work of copying, printing, scanning, managing paper and finishing thanks to flexible options for expansion* and intuitive user guidance. The systems are operated via a large colour touch display that you can adapt to suit your individual requirements.

The new systems are naturally very energy-efficient and so help to protect the environment thanks to the 'Skip Blank Pages' function, for example, where blank pages can be optionally filtered out when scanning and copying.



DIGITAL MULTIFUNCTIONAL SYSTEM

4056i / 5056i 6056i

Copy / Print / Scan / Fax

A3

HIGHLIGHTS:



Intelligent paper management: The systems offer a maximum paper capacity of 7,150 sheets from six paper feeds*. Paper weights of 52 to 300 g/m² and formats ranging from A6 to SRA3 are processed from the paper cassette. Optional finishing options allow you to output your print jobs with tri-folding for letters, as stapled and hole-punched documents or as dispatch-ready brochures. The 270-sheet dual scan original feeder* sets new standards for fast scanning in a single operation with gentle handling of original documents.



Vastly expandable: The HyPAS interface allows you to integrate optional software solutions into your system and also introduce your own customised software. Accessing the system via a smartphone or tablet isn't a problem either using a free Mobile Print app or the Apple AirPrint protocol. You can even scan documents in the cloud this way. In addition, the systems feature an NFC interface for direct printing from an Android smartphone or tablet*.



Fast document creation: You can start your first print job after a short warm-up time of only 17 seconds. Afterwards, the systems print up to 60 pages per minute. An optional scanning extension allows you to create text-searchable PDF files. Your texts are ready in no time at all without the hassle of retyping.



Simplest operation: If you know one, you know them all. The usability of our new systems has been further revised in accordance with this principle. Whether you're using the large 9-inch colour touch display or operating the standardised printer driver, you'll quickly find your way around all the systems of this product group, particularly due to the wide range of individual customisation options.

4056i / 5056i / 6056i

TECHNICAL DATA



General

Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser b/w
Original format	max A3 from platen glass
Copy/print speed	4056i: max 40 A4 pages/min and max 20 A3 pages/min 5056i: max 50 A4 pages/min and max 25 A3 pages/min 6056i: max 60 A4 pages/min and max 30 A3 pages/min
1st page (Copy/Print)	4.5/5.1 seconds* (4056i), 3.7/4.3 seconds* (5056i), 3.4/3.8 seconds* (6056i)
Warm-up time	17 seconds
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (cassette 1: A6R-A4, cassette 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing
Paper weights	Universal cassette 52-300 g/m ² , multi-bypass 52-300 g/m ² , duplex 64-256 g/m ²
Paper output	500 sheet A4
System memory	4 GB RAM, 8 GB SSD/320 GB HDD**
Continuous copying	1-999 copies
Zoom	25 %-400 % in steps of 1 %
Functions	Adjustable colour touch screen (9 inch), duplex, 1,000 management codes, skip blank pages etc.

Dimensions/Weight

Dimensions	790 x 602 x 665 mm (H x W x D)
Weight	approx. 82 kg

Environment

Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,750 W max, approx. 610/710/820 W in operation (4056i/5056i/6056i), approx. 40 W in stand-by mode, approx. 1 W in sleep mode, TEC value: 1.84/2.41/3.09 kWh/week (4056i/5056i/6056i)
Safety	GS/TÜV, CE

Print system

Type	Integrated within the system
Print format	A6R-SRA3
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi
Processor	Freescale QorIQ T1024 (Dual Core) 1,2 GHz
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2, Novell NetWare***, Linux, Mac ex OS 10.5
Emulations	PCL6 (5e, XL), KPD L 3 (PostScript 3 compatible), XPS, PDF, PRESCRIBE IIe
Functions	USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, barcode printing, Mobile Print (Android/iOS)/Apple AirPrint, Google Cloud Print

Scan system

Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	max 100 (simplex) or 180 (duplex) A4 originals/min in colour and b/w with DP-7110 (300 dpi)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, suitable for OCR
File types	TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS
Interfaces	10/100/1000BaseTX
Network protocol	TCP/IP
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP

Fax system 12

Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Fax memory	170 MB

Fax system 12

Abbreviated dial	2,000 numbers
One touch dial	1,000 numbers
Group dial	500 numbers
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception

Options

Original feeder	DP-7100 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7110 document processor with simultaneous duplex scanning (A6R-A3, capacity: 270 sheet A4, paper weight 35-220 g/m ²)
Platen cover	Platen cover type E (if document processor is not installed)
Finisher	DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 30 sheet A4), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7110 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7110, BF-730 brochure module for DF-7110 (max 16 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7110
Job Separator	JS-7100: 100 sheet
Paper feed	PF-7100 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7110 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck)
Other options	Scan extension kit (A), Data security kit (E), Internet fax kit (A), Card authentication kit (B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, IB-35 WLAN card, DT-730 (B) Document tray, NK-7100 Numeric Keyboard (10 keys), cabinet no. 76

*Depending on operating status.

For copy, print, scan, fax *optional

Specifications subject to change without notice.

Image shows machine with optional accessories.

The 4056i, 5056i and the 6056i are manufactured in accordance with the requirements of the Energy Star Program.

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.



HyPAS™



UTAX Norderstedt
www.utax.com